

(12) **UK Patent Application** (19) **GB** (11) **2 355 143** (13) **A**(43) Date of A Publication **11.04.2001**(21) Application No **9923916.2**(22) Date of Filing **08.10.1999**

(71) Applicant(s)  
**Nokia Mobile Phones Limited**  
**(Incorporated in Finland)**  
**Keilalahdentie 4, 02150 Espoo, Finland**

(72) Inventor(s)  
**Jonathan Sharp**

(74) Agent and/or Address for Service  
**Nokia IPR Department**  
**Nokia House, Summit Avenue, Southwood,**  
**FARNBOROUGH, Hampshire, GU14 0NG,**  
**United Kingdom**

(51) INT CL<sup>7</sup>  
**H04M 1/274 1/247**


(52) UK CL (Edition S )  
**H4L LEUF**  
**H4K KFH**

(56) Documents Cited  
**GB 2293474 A EP 0901262 A2 EP 0740447 A2**

(58) Field of Search  
**UK CL (Edition R ) H4K KFH , H4L LEUF**  
**INT CL<sup>7</sup> H04M 1/247 1/274**  
**On-Line - EPODOC, JAPIO, WPI**

(54) Abstract Title  
**Fast scrolling through data by simultaneous depression and displacement of user input device**

(57) A portable electronic device comprises a user input device capable of adopting at least three pre-determined positions, each of which enables an associated function to be actuated, a device for presenting information to a user, and a processor for receiving inputs from the user input device and altering the operating state of the portable electronic device accordingly. The portable electronic device is operable to scroll through information items presented to a user, the user input device being arranged to present at least two scrolling speeds. A first scrolling speed is selected when the user input device is placed in a first pre-determined position and a second scrolling speed is selected when the user input device is placed in the first pre-determined position and pushed into the portable electronic device. Preferably the user input device is a joystick, 28.

**FIG. 2a**

1 / 16




FIG. 1a





FIG. 1b



3 / 16




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8








FIG. 10




FIG. 11






FIG. 12



(a)



FIG. 13 (b)






FIG. 15




FIG. 16




FIG. 17a




FIG. 17b




FIG. 18a





FIG. 18b





### **A PORTABLE DEVICE**

The present invention relates to a portable device. In particular, it relates to  
5 the user interface of a portable device, such as a radio communications  
device.

There is currently a trend to strive towards the miniaturisation and wearability  
of portable devices. Particularly where phones are concerned, this results in a  
10 trade off against the ergonomics and ease of use of a conventional handset.  
One option is to compromise on the functionality of the device. However,  
another is to develop a new user interface that still supports typical features,  
such as phone calls, messaging and paging in an easily accessible way.

15 In accordance with the invention there is provided a portable electronic device  
comprising a user input device capable of adopting at least three pre-  
determined positions, each of which enables an associated function to be  
actuated, and of adopting two pre-determined positions simultaneously, a  
device for presenting information to a user, a processor for receiving inputs  
20 from the user input device and altering the operating state of the portable  
electronic device accordingly, wherein the portable electronic device is  
operable to scroll through information items presented to a user, the user  
input device being arranged to present at least two scrolling speeds, wherein  
a first scrolling speed is selected when the user input device is placed in a first  
25 pre-determined position and a second scrolling speed is selected when the  
user input device is placed in the first pre-determined position and a second  
predetermined position at the same time.

Preferably the second scrolling speed is selected when the user input device  
30 is placed in the first pre-determined position and pushed into the portable  
electronic device.

Preferably the user input device is a joystick.

For a better understanding of the present invention and to understand how the same may be brought into effect reference will now be made by way of example to the enclosed drawings in which:

- 5    Figure 1a is a front perspective view of a phone in a closed configuration;  
     Figure 1b is a side perspective view of the phone in a closed configuration;  
     Figure 2a is a front perspective view of the phone in an open configuration;  
     Figure 2b is a side perspective view of the phone in an open configuration;  
     Figure 3 is a schematic illustration of the phone;
- 10   Figure 4 is an illustration of the joystick of the phone;  
     Figure 5 illustrates the Menu structure in the phone;  
     Figure 6 illustrates a first method of data entry in accordance with the  
     invention;  
     Figure 7 illustrates a second method of data entry in accordance with the  
15   invention;  
     Figure 8 is a front perspective view of the phone in an open configuration;  
     Figure 9 illustrates a third method of data entry in accordance with the  
     invention;  
     Figure 10 illustrates a fourth method of data entry in accordance with the  
20   invention;  
     Figure 11 illustrates a method of variable scrolling speed in accordance with  
     the invention;  
     Figure 12 is a flow chart illustrating the multiple functionality of an on/off  
     switch of the phone;
- 25   Figure 13 illustrates various idle screens;  
     Figures 14 and 15 illustrate the functionality of an easy access button; and  
     Figure 16 illustrates various message screens.  
     Figure 17a illustrates how message functions can be accessed through the  
     Menu 50;
- 30   Figure 17b illustrates various formats that a displayed message or displayed  
     caller details may take;  
     Figure 18a illustrates how a message may be read when received with the  
     cover open;

Figure 18b illustrates how a message may be read when received with the cover closed using the easy access key and then optionally opening the cover;

Figure 18c illustrates how a message may be read when received with the cover closed without using the easy access button but by opening the cover.

5     Figures 1 and 2 illustrate a phone 2. The phone has a body portion 4 and a cover portion 6 connected by a hinge 5. The cover is movable between a closed position as illustrated in Figures 1a (front perspective) and 1b (side perspective) and an open position as illustrated in Figures 2a (front perspective) and 2b (side perspective).  
10

The body portion 4 includes a back face 7 which forms the back of the phone, lateral side faces 8a and 8b which form the sides of the phone, an upper side face 10 which forms the top side of the phone, a lower side face 12 which forms the bottom side of the phone, and a front face 14 which is exposed when the cover is in the open position and concealed when the cover is in the closed position. The body has: an antenna 16 on its upper side face 10; a microphone 18 on its lower side face 12; an open-cover button 20, a voice dial button 22, and an on/off button 24 on its side faces 8; and has a display 26 and a user input device 28 which is preferably a joystick on its front face 14.  
15     The buttons are user actuatable. The body also has a hinge switch 30 (not shown) which detects the position of the cover, being actuated when the cover opens and closes.  
20

25     The cover portion 6 has an exterior surface 32 which is accessible when the cover is in the closed position and an interior surface 34 which is inaccessible when the cover is in the closed position but is exposed when the cover is in the open position. The cover portion has on its exterior surface 32 an easily accessible button 36 and a speaker 38. The cover portion has on its interior surface 34 a speaker 40. The cover also has an aperture 42 extending all the way through the cover. The aperture is positioned and sized so that when the cover is in the closed position only a first portion 26a of the display 26 is visible through the aperture 42 to the user. The aperture may be covered with  
30

a transparent material to allow the user to see the first portion of the display 26a.

When the cover is in the closed position the interior surface 34 of the cover  
 5 abuts with the front face 14 of the body 4. The cover is arranged and sized to  
 enclose the input device 28 and display 26 to prevent access by the user. A  
 portion 26a of the display 26 may, however, be viewed by a user through the  
 aperture 36.

10 When the cover is in the open position the front face 14 of the body and the  
 interior surface 34 of the cover 6 form an oblique angle of between 135 and  
 175 degrees. In this configuration the whole of the display 26 is exposed, the  
 user input device 28 is exposed and the microphone 18 on the lower side face  
 12 of the body 4 and the speaker 40 on the interior surface 34 of the cover 6  
 15 are at their maximal separation.

The dimensions of the phone in this example are : length 60mm , width  
 40mm depth 20mm approx. The display is 2.1 x 1.4 cm (84x48 pixels).

20 Figure 3 is a schematic illustration of the phone 2. The phone 2 has the  
 previously described antenna 16, voice dial button 22, on/off button 24, input  
 device (joystick) 28, hinge switch 30, easily accessible button 36, microphone  
 18, display 26, speakers 40 and 38. In addition the phone has a processor  
 44, a transceiver 46 and a memory 48. The antenna 16 is connected to the  
 25 transceiver 46. The transceiver has reception circuitry for receiving radio  
 frequency signals encoded with data. It processes the received signals as is  
 known in the art to provide the data in digital form to the processor 50. This  
 data may be a voice message or part of a phone conversation in which case  
 the processor controls the speaker 40 to provide an audible output to the user.  
 30 Alternatively the data may be part of an alphanumeric message in which case  
 the processor 44 is operable to provide the message on the display. The  
 transceiver has transmission circuitry which is provided with digital data from  
 the processor 44 which may have been input via the microphone 18 or via the  
 input device 28 as alphanumeric characters. The transmission circuitry

produces radio frequency signals encoded with that data. The processor is connected to memory 48 to which it can write and from which it can read. The memory 48 typically stores software which controls the functioning of the processor and the phone. In particular the software controls how the processor responds to inputs and what outputs it provides.

The processor is connected to the display 26 and to the speakers 40 and 38. It controls the output provided by these devices.

The processor is arranged to receive an input from the microphone 18, the input device (joystick) 28, the hinge switch 30, the on/off button 24, the voice dial button 22 and the easily accessible button 36.

The open cover button 20 is not illustrated in Figure 3 as it opens the cover by mechanical as opposed to electrical action. The natural or low energy configuration for the phone is when the cover is open. The cover is biased to be in the open position. When a user closes the cover they rotate the cover on its hinge against that bias and bring the cover and body into contact. The cover is latched in this closed position. Activating the open cover button releases the latch and the cover springs open.

The antenna 16, transceiver 46, processor 44, memory 48, display 26, speaker and microphone 18 are standard features of a phone. Previously such features have operated in combination with a keypad to provide the standard functions of a phone including making a call either via a phone book or by direct character entry, receiving a call, creating and sending a message, reading a received message and maintaining a phonebook. However, in the phone 2, the features operate in combination with the joystick 28 to provide these standard functions.

Previously in the NOKIA 6110 telephone the keypad had 12 alphanumeric keys, two soft keys whose function changes and a scroll key. The functions of that phone are accessed through a Menu which is navigated using the soft

keys and the scroll key. In the phone 2, the functions of the phone are accessed through a Menu which is navigated using the joystick 28.

Figure 4 illustrates the joystick 28 which can be moved with a user's thumb.

5 The joystick can be pushed forward (towards the display) while simultaneously pushed to the left or right, pushed to the left or right while simultaneously pushed up or pulled back (towards the microphone), and pulled back while simultaneously being pulled left or right. In addition to each of the above movements the joystick may be simultaneously pushed inwards  
10 towards the face 14. The joystick 28 has a resting position and it is resiliently biased so that it returns to its resting position when the user has moved it or depressed it and then released it.

The joystick operates in two different modes. The joystick operates by default  
15 in "navigation" mode except when it is in "text editing" mode. In navigation mode there are five independent mutually exclusive activation states for the joystick.

When the joystick is pushed up, the processor performs an upward scrolling  
20 function within the current level of the Menu and updates the display accordingly. When the joystick is pulled back, the processor performs a downward scrolling function within the current level of the Menu and updates the display accordingly. These scrolling functions are the same as those scrolling functions in the NOKIA 6110. When the joystick is pushed to the left,  
25 the processor exits to the previous higher level in the Menu. When the joystick is pushed to the right, the processor presents on the display the options available to the user but in the Idle Mode it brings up the Menu. When the joystick is pushed inwards the processor enters the next level of the Menu or if there are no further levels it will display the options available to the user.

30

Figure 5 illustrates the layout of a Menu 50. When the phone is first switched on it enters the Idle state 54 in which it waits to receive a call or for user actuation. The joystick is in navigation mode. Pushing the joystick to the right enters the Menu 50. The Menu has on its first level 52 seven selectable items.

These items are: Number Dial 521 which allows the user to input a number or select a number from memory for dialling; Call Divert 522 which includes options for diverting an incoming call to another number; Settings 523 which includes settings related to calls, phone and security; Profiles 524 which includes options for a user to customise the modes of phone use; Names 525 which is an editable phonebook from which calls can be made; Call Register 526 which includes a record of phone calls made; and Messages 528 which includes options for reading and composing text messages. The user can move from one item to an adjacent item by pushing the joystick up or down.

10 The user can select an item and enter the second level 53 of the menu by pushing the joystick in. The user can return to the idle state from the first level 54 by pushing the joystick to the left.

The Menu items are the same as those in the NOKIA 6110 except that the joystick is used to navigate the Menu 100 and that due to the absence of an alphanumeric key keypad a new Number Dial item 521 is provided and new alphanumeric character entry methods are provided within each of the items where necessary.

20 In Idle mode the joystick has several pre-defined modes of operation. Pulling the joystick back causes the Names menu 525 to be displayed. Pressing the joystick inwards results in a shortcut to redial the last number dialled. Pressing the joystick inwards when an alphanumeric message is received causes the phone to display the Message "In Box" to read the message.

25 Pressing the joystick inwards when an incoming call is received causes the incoming call to be answered.

The "text editing" mode of the joystick is active when alphanumeric character entry is required. In this mode the joystick operates in the same manner as an integrated cursor control device in the keyboard of a portable computer in that it controls the position of a cursor or similar selector on the display 26. The joystick can additionally be pressed to accept the selected character(s).



In "text editing" mode, a short press of the joystick to the left results in the deletion of the previous character. A long press to the left (1-2 seconds) causes the deletion of all the text entered so far. In this case the phone subsequently reverts to idle mode.

5

A call may be made using the phone via the Names item 525, via Number Dial item 521 or via voice dial.

10 An incoming call may be answered, when the phone is in the closed configuration, by opening the cover. An incoming call may be answered when the phone is in the open configuration by pressing the joystick inwards. Closing the cover or by pressing the joystick inwards ends the call. When the cover is open, pushing the joy stick to the left rejects the call. The content of the display is the same when an incoming call is received irrespective of  
15 whether the cover is open or closed.

Turning now to the menu structure as shown in Figure 5, further details of the menu structure will be described with reference to Figure 6.

20

A mixed menu of characters and operands for functions of the phone(e.g. to make a call) is used. In this case, the joystick is used to navigate to the Number Dial menu which is then selected by pushing the joystick inwards. A menu is displayed on the display and a user selects the numerical characters  
25 by pushing forward and pulling back the joystick as appropriate. Once the number input is complete, the user selects the Call operand item from the menu and the call is established.

Figure 6 shows the display 26 displaying the "Number Dial" menu item 521. In  
30 figure 6 a left arrow indicates that the joystick is pushed to the left, a right arrow indicates that the joystick is pushed to the right, an up arrow indicates that the joystick is pushed forward, a down arrow indicates that the joystick is pulled back and the symbol • indicates that the joystick is pushed inwards. A

user selects the Number Dial option by pushing the joystick inwards (602) as described previously.

5 The display then changes to a text input mode with a menu 60 on the right-hand side of the display. The items of the menu 60 comprise both alphanumeric characters and operands, e.g. Call, OK, Name, Add etc. These operands can be represented textually or graphically as shown in Figure 6. The icon 66 of a phone indicates the call operand. Thus a user can access the required functionality of the phone without having to move to a separate  
10 menu to carry out an action.

To select from the menu 60, a user scrolls through the menu (604) by pushing the joystick forward (if movement up the menu is required) or pulling the joystick back (if movement down the menu is required). Each item in the  
15 menu 60 is highlighted at the bottom right-hand corner of the display as the menu is scrolled. When the required alphanumeric character is highlighted, the user selects the character (606) by pushing the joystick inwards. The selected character 62 is then displayed on the left-hand side of the display 26, adjacent the menu 60. This action is repeated (608) until the text input is  
20 completed.

When the user has finished inputting the number, the user selects the phone icon 66 from the menu 60 by pushing the joystick inwards (610). The display 26 then changes (612) to indicate that this operand is being performed and  
25 the device proceeds to try to establish the call.

As described previously, pushing the joystick to the right at any time (614) causes the display of options available to the user at that time and pushing the joystick to the left at any time (616) causes the current menu to be exited.

30 Figure 7 shows the menus available when the Name menu 525 is selected. The user is presented with the "Add Name" option 72 and inputs a name using the alphanumeric characters in the menu 70. Again the items of the menu 70 comprise both alphanumeric characters and operands, e.g. OK, Caps (for capital letters), Insert, Exit etc. Once the name has been input, the

user then selects from the menu 70 the required operand e.g. OK. When this operand is selected (702) the user is presented with the "Add Number" option 74 and a menu 76 of operands and numeric characters. Once the number to be associated with the name has been entered, the user selects the required  
5 operand from the menu 76 e.g. OK and the name and number are stored (704) in the memory 48 of the phone as a phone book entry. Suitable operands are OK, Insert and Cancel.

Alternatively the menus 60, 70, 76 may be provided at the bottom of the  
10 display in a horizontal manner. The menu items may be displayed a line at a time with an up/down movement of the joystick resulting in the display of successive lines of menu items and a left/right movement of the joystick resulting in the highlighting of successive items in the line of the menu 60.

15 The joystick may also be used to input data directly, without the requirement for a menu of options to be displayed on the screen. For instance, the input device 28 may be used to input numeric characters. Figure 8 shows an example of such a joystick. In Figure 8, feedback to the user about the characters available is provided around the joystick, on the front face 14 of the  
20 body 4. Alternatively this feedback may be provided on the display 26.

In this mode, a user is prompted to use the joystick to input numbers, for instance by an image 90 on the display 26 (see Figure 9). If the user pushes the joystick forward the numbers 1, 2 or 3 may be selected; if the user pushes  
25 the joystick to the right the numbers 4, 5 or 6 may be selected; if the user pulls the joystick back the numbers 7, 8 or 9 may be selected; if the user pushes the joystick to the left the number 0 and the characters \* and # may be selected. Pushing the joystick repeatedly in one direction causes the characters available to be scrolled through; a character may be selected  
30 either if a pre-determined time has elapsed without any further input from a user or by the user pushing the joystick inwards (902) for a short time.

Once the user has input the number by successively pushing/pulling the joystick and then pushing the joystick inwards (904-908), the user pushes the

joystick inwards for a relatively long time (e.g. 1-2 seconds) (910). This causes a menu 94 to be displayed. The user selects the appropriate action by pushing the joystick inwards (912) and the device carries out the action.

- 5 In a similar manner, the joystick may be used to input alpha characters. In this mode, a user is prompted to use the joystick to input alpha characters, for instance by an image on the display 26. If the user pushes the joystick forward the characters a, b, c, d, e, f, g may be selected; if the user pushes the joystick to the right the characters h, i, j, k, l, m may be selected; if the  
 10 user pulls the joystick back the characters n, o, p, q, r, s, t may be selected; if the user pushes the joystick to the left the characters u, v, w, x, y, z and "space" be selected. Pushing the joystick repeatedly in one direction causes the characters available to be scrolled through; a character may be selected either if a pre-determined time has elapsed without any further input from a  
 15 user or by the user pushing the joystick inwards for a short time.

The device may be arranged to default to the mode of data input. Alternatively it may be a mode that is activated by the user selecting the option in the device's Profiles 524.

20

- A further method of data input will now be described with reference to Figure 10. A user scrolls through a list of characters 100 in blocks of three 102 by pushing the joystick forward or pulling the joystick back. The user selects a character by then pushing the joystick to the right (104) until the required  
 25 character is highlighted and then pushing the joystick inwards (105) for a short time. When the user has inputted the entire item, the user pushes the joystick inwards (106) for a relatively long time. A menu 108 of actions is then displayed and the user selects the appropriate one by pushing the joystick inwards.

30

According to a further aspect of the invention, the speed of scrolling is determined by the position of the joystick as illustrated in Figure 11. A selectable item is highlighted as the items in a menu are scrolled though. A single movement of the joystick up or down (110) causes a display (menu or

text) to be scrolled through by one line at a time. Thus in Figure 11 the highlighted item will change from Bruce to Carl. Pushing the joystick inwards (111) selects this item.

- 5 Moving the joystick up or down and holding it in this position (112) causes the item to be scrolled through continuously e.g the names Bruce, Carl, Diana, Fiona, ... Graham, Guy will be scrolled though in a continuous manner until the joystick is released. Pushing the joystick inwards (111) selects the highlighted item.

10

- Moving the joystick up or down and holding it in this position whilst also pressing in on the joystick (113) results in a higher speed of continuous scrolling. Thus the display changes from Graham, Guy, Helen to further down the menu (e.g. Susa, Tom, Trevor) faster than previously. Thus a user can
- 15 quickly scroll through a long list until the general region of the required item is located and then release the inward pressure on the joystick to cause the speed of scrolling to reduce. The joystick can then be held in the up (or down) position until the required item is located. The joystick is released and pushing the joystick inwards (111) then selects the highlighted item.

20

- The hinge switch 30 is activated when the cover 6 is opened and is activated when the cover is closed. The switch detects when the interior surface 34 of the cover 6 makes a specific acute angle (for example 5 degrees) with the front face 14 of the body 4. The processor maintains a register which changes
- 25 state when the hinge switch is activated. The processor is therefore aware of whether the cover is in the open or closed position. The processor also detects via the hinge switch 30 when the cover is opened and when the cover is closed.

- 30 Turning now to the on/off button 24 of the phone, illustrated in Figure 3, this button has multiple functionality. In this embodiment, the functionality is determined by the manner of actuation of the button 24 and/or the state of the phone. Figure 12 illustrates how the processor 50 determines which function to perform when the on/off button is actuated.

The processor waits for actuation of the on/off button 24 by the user (Step 120). When the button is actuated, the processor 50 proceeds to Step 121. In this case, the processor 50 responds differently when the button is depressed and released (short press) compared with when the button is held in a depressed position and then released (long press). The processor senses the input from the button. When the button is activated the processor starts a timer. When the button is deactivated the processor stops the timer. If the count of the timer is less than a predetermined threshold the processor determines that the user employed a short press and wishes to access a function or function associated with that method. Consequently, the processor moves to step 122.

Alternatively, if the count of the timer is equal to or more than a predetermined threshold (typically 1-2 seconds) the processor determines that the user employed a long press (Step 125). In this case, a long press is indicative of a power off function, and consequently, the processor performs this function in a conventional manner.

Turning back now to Step 122, the short press is not indicative of a single function. Instead, the function depends upon the state of the phone. If not in Idle mode 54 then the processor exits all menus and returns the phone to Idle mode 54 (Step 124). On the other hand, if the phone is already in Idle mode 54 then the processor performs a shortcut into the profiles menu (Step 123) which may also be entered via item 124. When in the Idle mode the on/off button has the same functionality as that in the NOKIA 6110 in the Idle mode.

The voice dial button 22 allows a user to dial a number using voice commands when the phone is in the Idle state.

30

In this embodiment, the display contains different information when in the idle state, depending on the circumstances of the phone. Figure 13 illustrates different examples: Figure 13 (a) shows different information presented on the display depending on whether the cover is in the open or closed position, and

Figure 13(b) shows alternative idle screens when the cover is in the closed position a headset is coupled to the phone.

Figure 13(a) illustrates the idle screen as it appears on a visible area 131 of the display and on the whole display 132, when the cover is in the closed position. It also illustrates the screen as it appears on the display when the cover is in its open position.

As can be seen, when the cover is in the closed position, the content of the idle screen is reduced from that apparent when the cover is in its open position, to key information such as network signal strength, battery and time and this information is centred in the display. The format as opposed to the content is also changed. In the closed position the battery and signal indicators are of a rounded design extending towards the centre of the display, whereas in the open position they are of a linear design. The content of the screen is therefore more centred, simpler, clearer and contains less information when the cover is closed compared to when it is open.

Figure 13(b) illustrates idle screens 134 and 135 as they appear on a visible area of the display when a headset is coupled to the phone. In this case, for an initial period, a first idle screen 134 is presented, that comprises the word "Headset" and icon of a headset. After this period, the processor controls the display to present a second idle screen 135 in which the word "Headset" is replaced with the time.

Idle mode screen may depend upon the placement or use of the product. For example, if the phone is a wrist-worn device its idle screen may have prominent watch functions such as time zones, alarms or analogue looking clock faces. Similarly, personalisable wearable products may have user defined bitmaps.

Easy access button 36 has multiple functionality when the phone is in the closed configuration and no function, it is disabled, when the cover is opened. In this context, multiple functionality does not mean that the button has

multiple functions simultaneously, it does not. At any time, the button 36 has only a single function. However, that single function may be one of many depending upon the state of the phone. Generally, actuation of the button provides the most likely response to a given situation. It does not delete or  
5 change things. If the alarm rings, activation ends the ringing. If there is an incoming call activation mutes the ringing. If a message has just been received activation opens the message. If a call has just been missed activation gives the caller's details. If the phone is in the Idle state, activation redials the last dialled number.

10

Figures 14 and 15 illustrate how the processor 50 determines which function to perform when the easy access button 36 is actuated.

Firstly, the processor 50 determines whether the phone's cover is in its closed  
15 position (Step 141). If it is, the processor waits for actuation of the easy access key by the user (Step 142). However, if the phone is in its open configuration, then the processor disables the easy access key (Step 144). This disablement may be complete or partial disablement of the phone. Complete disablement may, for example include the processor not responding  
20 at all to key actuation, so that even display backlighting, audible indications and the like, which generally occur upon key actuation, are not performed. Partial disablement, on the other hand, may merely be disablement of the actual function or functions associated with the key.

25 If the processor detects actuation of the easy access key, the processor proceeds from Step 142 to Step 143. Step 143 includes the determination by the processor of the state of the phone and the performance of the consequential function. This is further explained with reference to Figure 15.

30 In this embodiment, the easy access key has a plurality of functions, depending upon the phone being in one of five states when the key is actuated. These five states are incoming call, alarm, headset attached, idle and message received, as explained briefly above.



If the processor 50 determines that, when the key is actuated, the phone is either in the incoming call state (decision 151) or the alarm state (decision 152), then the processor disables the audible indicator or speaker 38 (Step 156). Alternatively, if the processor 50 determines that, when the key is actuated, a headset is attached to the device (decision 153) or the phone is in the idle state (decision 151), then the processor accesses the last number redial menu. It also displays the last number redial option on the display 26.

The processor causes the received message to be displayed (Step 158) if the phone is in the message received state (decision 155) when the easy access key is actuated. Next, the processor determines whether the message displayed is the only one received. (Step 159). If it is, then once the message has been fully displayed, the processor returns the phone to its idle state (Step 146). However, if there is a further message, the processor waits for a further actuation of the easy access key (Step 145). ). If the key is not actuated within a predetermined period, then the processor returns the phone to its idle state (Step 146). However, on the other hand, if the key is actuated within the predetermined period, then the further message is displayed (Step 158). Steps 158, 159 and 145 are repeated until all messages have been displayed or the easy access key is not actuated within the predetermined period.

Figure 16 illustrates two message screens, as viewed when the cover is in its closed position. When a message is received, the state of the phone changes to the message received state. In response to this change, the processor causes the display to present the content as illustrated by the view 161. Then, once the easy access key (external button) is actuated, the message starts scrolling across the display, as illustrated by the view 162. In this embodiment, the information displayed contains the name or number of the message sender, followed by the message. Actuating the key again will cause the next message to be scrolled across the display, and so on. Once the last message has scrolled, a further actuation of the easy access key results in the phone returning to its idle state.

The procedure for dealing with a missed call or calls is similar to that for dealing with a received message or messages. When a call has been missed the caller details are stored in the phone's memory and the state of the phone changes to a missed call state. In response to this change the processor

5 causes the display to present text indicating that a call or calls have been missed – e.g. “1 call missed”, “2. calls missed” etc. Then, when the easy access key is actuated, the processor retrieves the caller's details from memory and provides them as text scrolling across the display. The callers details are also be displayed automatically if the cover is opened instead of

10 pressing the easy access key. The details may be displayed in a static or scrolling format as described later for the display of text messages (Figure 17b).

Some functionality associated with movement of the cover has already being

15 described such as: answering an incoming call by opening the cover, ending a call in progress by closing the cover and the change in the content of the display when the phone is in the idle mode effected by opening and closing the cover. A further function associated with the active flip is when the phone is within an item of the menu, closing the flip will return the phone to the idle

20 state. Opening the cover also has functionality in connection with reading received messages.

The process of accessing messages through the menu structure is illustrated in Figure 17. Selecting Messages 528 from within the Menu 50 by scrolling up

25 or down using the joystick and then pushing the joy stick inwards, displays all the messaging options 171: Inbox which stores received messages , Write which allows the composition of messages, Outbox which stores sent messages, Templates which stores pro-form messages or the like and Archive in which messages may be stored from the Inbox and Outbox. The

30 icon next to In box contains an arrow indicating it contains a new (unread) message. Selecting the Inbox within the messaging options 171 by scrolling up or down if necessary to highlight “Inbox” and the then pressing the joystick in, displays the contents of the Inbox 172. The contents of the Inbox is a number of messages. The icon next to Colin indicates that this is an unread

message. Selecting the message Colin from within the Inbox 172 by scrolling up or down as necessary using the joystick and then pushing the joystick in, displays the contents of the message 173. Pressing the joystick in again provides a number of options 174 such as erase, edit, archive etc. Selection  
5 of the appropriate item by scrolling using the joystick and then pushing the joystick in performs the appropriate function. In the example, erase is selected and the erase function performed. The display then returns to the Inbox 172 if there are any remaining unread messages or to the options 171 if there are not.

10

The format of the message displayed in 173 may take various forms as illustrated in Figure 17b. The message may be static 176, with the user able to scroll up and down through the message by pushing the joystick up or pulling it down. The message may occupy several lines with it scrolling through the  
15 display word by word 177. For example, as a word disappears from the screen on the first line at the top left the whole message moves so that the next word is positioned at the top left hand corner of the display and one or more words are appear on the display at the bottom right hand corner. As another alternative 178 the message may occupy a single line and scroll  
20 across the screen one character at a time as if the display where a fixed window with the message passing by as if printed on a tape moving at a constant speed past that window.

When a message is received while the cover is open, the processor enters a  
25 message received state and the Idle display changes to indicate that a message has been received. This is illustrated as 180 in Figure 18. Pushing the joystick inwards enters the Inbox 172. Pushing the joystick to the left, returns the display to the Idle mode. The up, down and right movements of the joystick have the same functions as in this received message state as in the  
30 Idle Mode.

When a message is received and the cover is closed there are two ways of accessing the message: pressing the easy access key and opening the cover.

As previously described with reference to Figure 16, when a message has been received with the phone in the closed configuration, and the easy access key (external button) is actuated, the content of the message is scrolled across the display portion as a single line one character at a time in a manner similar to that described in relation to format 178 of Figure 17b. If the cover is then opened the format of the display changes. This is illustrated in Figure 18b. The text no longer scrolls across the display in a single line, but is preferable displayed in a static format 176 or scrolling format 177 several lines at a time. If the message is displayed in a static format 176, it does not scroll automatically but the contents can be viewed by scrolling through the message using the joystick. Pushing the joy stick upwards scrolls upwards through the message. Pulling the joystick downwards scrolls downwards through the message.

When a message is received and the cover is closed, the phone enters a message received state 161 as illustrated in Figure 16. If the cover is then opened, the phone then enters state 73 illustrated in Figure 17a and displays the content of the message received. The format of the content may vary and may be static 176, multiple line and scrolling 177 or single line and scrolling as previously described with reference to Figure 17b. This process is illustrated in Figure 18c.

The voice dial button 22 allows a user to dial a number using voice commands when the phone is in the Idle state.

25

Although the user input device 28 has been described with reference to a joystick, the invention is also applicable to other user input devices e.g. a roller or rocker key that is moveable up, down, left, right and inwards.

30 The present invention may include any novel feature or combination of features described herein either explicitly or implicitly or any generalisation thereof whether or not it relates to the present claimed invention or mitigates any or all of the problems addressed. In view of the foregoing description it will

be evident to a person skilled in the art that various modifications may be made within the scope of the invention.

## Claims

1. A portable electronic device comprising  
a user input device capable of adopting at least three pre-determined  
5 positions, each of which enables an associated function to be actuated, and of  
adopting two pre-determined positions simultaneously,  
a device for presenting information to a user,  
a processor for receiving inputs from the user input device and altering  
the operating state of the portable electronic device accordingly,  
10 wherein the portable electronic device is operable to scroll through  
information items presented to a user, the user input device being arranged to  
present at least two scrolling speeds, wherein a first scrolling speed is  
selected when the user input device is placed in a first pre-determined  
position and a second scrolling speed is selected when the user input device  
15 is placed in the first pre-determined position and a second predetermined  
position at the same time.
2. A device according to claim 1 wherein the second scrolling speed is  
selected when the user input device is placed in the first pre-determined  
20 position and pushed into the portable electronic device.
3. A device according to claim 1 or 2 wherein the user input device is a  
joystick.
- 25 4. A portable electronic device substantially as described herein with  
reference to figure 11 of the accompanying drawings.
5. A method of scrolling through data substantially as described herein  
with reference to figure 11 of the accompanying drawings.



Application No: GB 9923916.2  
Claims searched: 1 to 3

Examiner: Jared Stokes  
Date of search: 26 March 2000

**Patents Act 1977**  
**Search Report under Section 17**

**Databases searched:**

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.R): H4K (KFH)  
H4L (LEUF)

Int Cl (Ed.7): H04M (1/247, 1/274)

Other: On-Line - EPODOC, JAPIO, WPI

**Documents considered to be relevant:**

Category	Identity of document and relevant passage	Relevant to claims
A	GB 2 293 474 A (NEC) See abstract	-
A	EP 0 901 262 A2 (Nokia) See abstract	-
A	EP 0 740 447 A2 (Nokia) See abstract	-

X Document indicating lack of novelty or inventive step	A Document indicating technological background and/or state of the art.
Y Document indicating lack of inventive step if combined with one or more other documents of same category.	P Document published on or after the declared priority date but before the filing date of this invention.
& Member of the same patent family	E Patent document published on or after, but with priority date earlier than, the filing date of this application.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☒ **BLACK BORDERS**

☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

☐ **FADED TEXT OR DRAWING**

☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

☐ **SKEWED/SLANTED IMAGES**

☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

☐ **GRAY SCALE DOCUMENTS**

☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**

☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**